



The strong but not so silent type, as each tile tells the story of weathered stone—rich with visual depth, natural contrasts, and earthen hues

INKJET COLOR BODY RECTIFIED FLOOR & WALL GLAZED PORCELAIN STONEWARE

IVORY



GIFO2424IV
24" x 24" Rectified Field Tile

BLACK



GIFO2424BL
24" x 24" Rectified Field Tile

GREY



GIFO2424GR
24" x 24" Rectified Field Tile


TAUPE



GIFO2424TP
24" x 24" Rectified Field Tile



GIFO1224IV
12" x 24" Rectified Field Tile



GIFO1224BL
12" x 24" Rectified Field Tile




GIFO1224GR
12" x 24" Rectified Field Tile



GIFO1224TP
12" x 24" Rectified Field Tile



GIFOMOSIV
12" x 12" Mosaic



GIFOMOSBL
12" x 12" Mosaic



GIFOMOSGR
12" x 12" Mosaic



GIFOMOSTP
12" x 12" Mosaic




GIFO424BNIV
4" x 24" Bullnose



GIFO424BNBL
4" x 24" Bullnose




GIFO424BNGR
4" x 24" Bullnose




GIFO424BNTP
4" x 24" Bullnose



GIFOMURIV
3" x 6" Mosaic



GIFOMURBL
3" x 6" Mosaic



GIFOMURGR
3" x 6" Mosaic



GIFOMURTP
3" x 6" Mosaic


PACKAGING

NOMINAL SIZE	PIECES PER BOX	SQ. FT. PER BOX	LBS. PER BOX	BOXES PER PALLET	SQ. FT. PER PALLET	WEIGHT PER PALLET
24" x 24" Rectified Field Tile	4	15.61	71.65	32	499.50	2292.81
12" x 24" Rectified Field Tile	7	13.67	62.83	32	437.40	2010.62
12" x 12" Mosaic	4	3.87	18.38	90	-	-
4" x 24" Bullnose	12	-	34.17	60	-	-
3" x 6" Mosaic	4	3.87	18.38	48	-	-

TECHNICAL SPECIFICATIONS

DESCRIPTION	RESULT	TEST METHOD (STANDARD)
PEI Rating	4	ASTM C-1027
Water Absorption	0.5%	ASTM C-373
C.O.F. (Dynamic)	0.42	ANSI A137.1
Chemical Resistance	Excellent	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Thickness	9 mm	Factory Provided

SHADE VARIATION AND APPLICATIONS

 V3 HEAVY VARIATION		RESIDENTIAL	COMMERCIAL	INDUSTRIAL
	Floor	•	•	•
Wall	•	•	•	
Countertop	•	•	•	